

Product type designation

IWLAN panel feedthrough N-Connect/N-Connect Female/Female
 N-Connect Female/female Panel feedthrough, cabinet bushing, 2.4 GHz and 5 GHz for Wall thickness max. 4.5 mm



Electrical data

Number of electrical connections	2
Type of electrical connection	N-Connect female/N-Connect female
Transmission frequency	0 ... 11 GHz
Impedance	50 Ω

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	-30 ... +100 °C
<ul style="list-style-type: none"> during storage 	-30 ... +100 °C
<ul style="list-style-type: none"> during transport 	-30 ... +100 °C
Protection class IP	IP68
Diameter	20.7 mm
Length	38 mm
Net weight	55 g

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes

Internet-Link

- to website: TIA Selection Tool <http://www.siemens.com/tia-selection-tool>
- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to the website: IWLAN <http://www.siemens.com/iwlan>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

11/11/2019