



Representative



Representative

**Catalog Number:** XPLFL236  
**Product ID:** 7TAD013340R0011  
**UPC Number:** 78620988441  
**EAN Number:** 05415022259834  
**Status:** Active

3/4 Inch x 36 Inch XP Flex Explosion Proof Flexible Coupling

- UL Listed for use in hazardous and wet locations.
- Corrosion-resistant, ideal for washdown areas.
- Flexible bronze construction with arc-resistant inner sleeve and brass fittings.
- Terminated with two threaded female end fittings and male close nipples.
- No bonding jumper required.
- Flexible design allows for use to make tight bends or allow for movement or vibration.

### North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Type	XP Flex Explosion-Proof Flexible Couplings-Hazardous Location
Special Features	No Bonding Jumper Required
Application	Explosion-Proof and Dust-Ignition-Proof for Use In Hazardous Locations
Standard	UL E193396, cULus
Trade Size	3/4 Inch
Length	36 in
Material	Brass
Color	Metallic

### European Specifications (ETIM)

ETIM	EC000939 Coupler for installation tubes
Material	Metal
Material quality	Other
Model	Thread
Two piece	N
With inspection opening and cover	N

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	36x2x2
Weight Uom	5.58 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000382
Technical Drawing / Data Sheet Canada	Available on Website

### Header

3D Model	Available on Website
----------	----------------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com