

\*\*\*\* Spare part \*\*\* Does not correspond to the current version of the standard. Charging station for Mobile Panel 277(F) IWLAN With lock For charging and storing the Mobile Panel 277(F) IWLAN Charging of 2 additional batteries



### Supply voltage

Type of supply voltage	24 V DC
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V

### Input current

Current consumption (rated value)	3.2 A
-----------------------------------	-------

### Power

Active power input, typ.	77 W
--------------------------	------

### Degree and class of protection

Degree of protection acc. to EN 60529	IP65
---------------------------------------	------

### Standards, approvals, certificates

CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes

### Ambient conditions

Ambient temperature during operation	
<ul style="list-style-type: none"> <li>Operation (vertical installation)</li> </ul>	0 to +40 °C

— For vertical installation, min.	0 °C
— For vertical installation, max.	40 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	60 °C
<b>Relative humidity</b>	
• Operation, max.	85 %

<b>Dimensions</b>	
Width	208 mm
Height	333 mm
Depth	75 mm

<b>Weights</b>	
Weight (without packaging)	1.1 kg

<b>Other</b>	
Usable in the following products	
• Product 1	<a href="#">6AV6645-0EB01-0AX1</a>
• Product 2	<a href="#">6AV6645-0EC01-0AX1</a>
• Product 3	<a href="#">6AV6645-0EF01-0AX1</a>
• Product 4	<a href="#">6AV6645-0GB01-0AX1</a>
• Product 5	<a href="#">6AV6645-0GC01-0AX1</a>
• Product 6	<a href="#">6AV6645-0GF01-0AX1</a>
• Product 7	<a href="#">6AV6645-0DD01-0AX1</a>
• Product 8	<a href="#">6AV6645-0DE01-0AX1</a>
• Product 9	<a href="#">6AV6645-0FD01-0AX1</a>
• Product 10	<a href="#">6AV6645-0FE01-0AX1</a>
• Product 11	<a href="#">6AV6645-0DB01-0AX0</a>
• Product 12	<a href="#">6AV6645-0DC01-0AX0</a>
• Product 13	<a href="#">6AV6645-0DD01-0AX0</a>
• Product 14	<a href="#">6AV6645-0DE01-0AX0</a>

**last modified:** 11/13/2019