

<b>Product type designation</b>	<b>CP 1613 A2</b> Communications processor CP 1613 A2 PCI card (32 bit; 33MHz/66MHz; 3, 3V/5V universal key) for connection to Industrial Ethernet (10/100 Mbit/s) with ITP and RJ 45-connection via HARDNET-IE S7 and S7-Redconnect. Operating system support see SIMATIC NET software
---------------------------------	--

Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s

Interfaces	
Number of electrical connections	2
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	
Type of electrical connection	RJ45 port / 15-pin ITP connection
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	

Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> <li>1 / from backplane bus</li> </ul>	5 V
<ul style="list-style-type: none"> <li>2 / from backplane bus</li> </ul>	12 V
Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> <li>at 5 V</li> </ul>	5 %
<ul style="list-style-type: none"> <li>at 12 V</li> </ul>	5 %
Consumed current	
<ul style="list-style-type: none"> <li>1 / from backplane bus / at DC / maximum</li> </ul>	0.45 A
<ul style="list-style-type: none"> <li>2 / from backplane bus / at DC / maximum</li> </ul>	0.5 A
Power loss [W]	4 W

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	5 ... 55 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-20 ... +60 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00
Module format	PCI
Width	21.6 mm
Height	107 mm
Depth	167 mm

Net weight	140 g
------------	-------

### Product features, product functions, product components / general

Number of plug-in cards of same design / plug-in / per PC station	4
Number of units / Note	-

### Performance data

#### Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	120

#### Performance data / S7 communication

Software / for S7 communication / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for S7/PG communication / maximum	120
Number of possible connections / for optimized S7 communication / maximum	40

#### Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	120
Number of configurable connections / per PC station	207

#### Performance data / PROFINET CBA

Software / for PROFINET CBA communication / required	Yes, PN CBA OPC server
Number of remote connection partners / with PROFINET CBA	228
Number of connections / with PROFINET CBA / total	10000

### Product functions / management, configuration, engineering

Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	No
• DCP	Yes
• LLDP	No
Configuration software / required	Included in the scope of delivery of the required software product
Configuration software / for PROFINET CBA / required	Yes, SIMATIC iMAP
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

- I&M2 - installation date No
- I&M3 - comment No
- I&M4 - signature No
- I&M4 - OEM data No

#### Product functions / redundancy

Software / for redundancy function / required Yes, HARDNET-IE S7-REDCONNECT for communication with SIMATIC S7 H systems

#### Product functions / time

Product function / SICLOCK support Yes

Protocol / is supported / NTP No

#### Standards, specifications, approvals

Standard

- for EMC 2004/108/EC
- for safety / from CSA and UL CAN/CSA C22.2 & UL 60950-1, UL 1950
- for emitted interference EN 61000-6-3, EN 61000-6-4
- for interference immunity EN 61000-6-1, EN 61000-6-2

Certificate of suitability

- CE marking Yes
- C-Tick Yes

#### Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <http://www.siemens.com/industrial-controls/mall>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

#### Security information

---

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

11/19/2019