




RIGID BODIES AND ASSEMBLIES

LR Assembly
N/A

C13



Part No.	QTY	Part No.	QTY	Part No.	QTY	Part No.	QTY	Part No.	QTY
1	1	1	1	1	1	1	1	1	1
2	1	3	1	4	1	5	1	6	1
7	1	8	1	9	1	10	1	11	1
12	1	13	1	14	1	15	1	16	1
17	1	18	1	19	1	20	1	21	1
22	1	23	1	24	1	25	1	26	1
27	1	28	1	29	1	30	1	31	1
32	1	33	1	34	1	35	1	36	1
37	1	38	1	39	1	40	1	41	1
42	1	43	1	44	1	45	1	46	1
47	1	48	1	49	1	50	1	51	1
52	1	53	1	54	1	55	1	56	1
57	1	58	1	59	1	60	1	61	1
62	1	63	1	64	1	65	1	66	1
67	1	68	1	69	1	70	1	71	1
72	1	73	1	74	1	75	1	76	1
77	1	78	1	79	1	80	1	81	1
82	1	83	1	84	1	85	1	86	1
87	1	88	1	89	1	90	1	91	1
92	1	93	1	94	1	95	1	96	1
97	1	98	1	99	1	100	1	101	1
102	1	103	1	104	1	105	1	106	1
107	1	108	1	109	1	110	1	111	1
112	1	113	1	114	1	115	1	116	1
117	1	118	1	119	1	120	1	121	1
122	1	123	1	124	1	125	1	126	1
127	1	128	1	129	1	130	1	131	1
132	1	133	1	134	1	135	1	136	1
137	1	138	1	139	1	140	1	141	1
142	1	143	1	144	1	145	1	146	1
147	1	148	1	149	1	150	1	151	1
152	1	153	1	154	1	155	1	156	1
157	1	158	1	159	1	160	1	161	1
162	1	163	1	164	1	165	1	166	1
167	1	168	1	169	1	170	1	171	1
172	1	173	1	174	1	175	1	176	1
177	1	178	1	179	1	180	1	181	1
182	1	183	1	184	1	185	1	186	1
187	1	188	1	189	1	190	1	191	1
192	1	193	1	194	1	195	1	196	1
197	1	198	1	199	1	200	1	201	1
202	1	203	1	204	1	205	1	206	1
207	1	208	1	209	1	210	1	211	1
212	1	213	1	214	1	215	1	216	1
217	1	218	1	219	1	220	1	221	1
222	1	223	1	224	1	225	1	226	1
227	1	228	1	229	1	230	1	231	1
232	1	233	1	234	1	235	1	236	1
237	1	238	1	239	1	240	1	241	1
242	1	243	1	244	1	245	1	246	1
247	1	248	1	249	1	250	1	251	1
252	1	253	1	254	1	255	1	256	1
257	1	258	1	259	1	260	1	261	1
262	1	263	1	264	1	265	1	266	1
267	1	268	1	269	1	270	1	271	1
272	1	273	1	274	1	275	1	276	1
277	1	278	1	279	1	280	1	281	1
282	1	283	1	284	1	285	1	286	1
287	1	288	1	289	1	290	1	291	1
292	1	293	1	294	1	295	1	296	1
297	1	298	1	299	1	300	1	301	1
302	1	303	1	304	1	305	1	306	1
307	1	308	1	309	1	310	1	311	1
312	1	313	1	314	1	315	1	316	1
317	1	318	1	319	1	320	1	321	1
322	1	323	1	324	1	325	1	326	1
327	1	328	1	329	1	330	1	331	1
332	1	333	1	334	1	335	1	336	1
337	1	338	1	339	1	340	1	341	1
342	1	343	1	344	1	345	1	346	1
347	1	348	1	349	1	350	1	351	1
352	1	353	1	354	1	355	1	356	1
357	1	358	1	359	1	360	1	361	1
362	1	363	1	364	1	365	1	366	1
367	1	368	1	369	1	370	1	371	1
372	1	373	1	374	1	375	1	376	1
377	1	378	1	379	1	380	1	381	1
382	1	383	1	384	1	385	1	386	1
387	1	388	1	389	1	390	1	391	1
392	1	393	1	394	1	395	1	396	1
397	1	398	1	399	1	400	1	401	1
402	1	403	1	404	1	405	1	406	1
407	1	408	1	409	1	410	1	411	1
412	1	413	1	414	1	415	1	416	1
417	1	418	1	419	1	420	1	421	1
422	1	423	1	424	1	425	1	426	1
427	1	428	1	429	1	430	1	431	1
432	1	433	1	434	1	435	1	436	1
437	1	438	1	439	1	440	1	441	1
442	1	443	1	444	1	445	1	446	1
447	1	448	1	449	1	450	1	451	1
452	1	453	1	454	1	455	1	456	1
457	1	458	1	459	1	460	1	461	1
462	1	463	1	464	1	465	1	466	1
467	1	468	1	469	1	470	1	471	1
472	1	473	1	474	1	475	1	476	1
477	1	478	1	479	1	480	1	481	1
482	1	483	1	484	1	485	1	486	1
487	1	488	1	489	1	490	1	491	1
492	1	493	1	494	1	495	1	496	1
497	1	498	1	499	1	500	1	501	1



Catalog #: RLR100

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.
N/A

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 1 in.

DRAWING DIMENSIONS

- Dimension A: 5.92 in.
- Dimension B: 2.68 in.
- Dimension C: 1.89 in.
- Dimension D: 1.82 in.
- Dimension E: 4.83 in.
- Dimension F: Tapped holes #8-32UNC-2B
- Dimension G: 1-11 1/2NPT
- Dimension H: 1.039 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm3): 12.0 (196.6)

PACKAGING

- Package Type: Carton
- Ship Carton Qty.: 5
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 60.00
- Ship Carton Length (in.): 7.00
- Ship Carton Width (in.): 4.75
- Ship Carton Height (in.): 8.13
- Ctn Weight (Lbs.): 3.00
- UPC Number: 092326213349
- I2of5: 30092326213340