

Product type designation

SCALANCE X101-1

SCALANCE X101-1, IE Media converter unmanaged 1x 10/100 Mbit/s RJ45 port, 1x 100 Mbit/s Multimode BFOC, LED diagnostics, error signaling Contact with Set pushbutton Redundant power supply, PROFINET-compliant securing collars, Manual available as a download available



Transfer rate	
Transfer rate	100 Mbit/s
Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
<ul style="list-style-type: none"> • for network components or terminal equipment • for signaling contact • for power supply • for redundant voltage supply 	<p>1</p> <p>1</p> <p>1</p> <p>1</p>
Type of electrical connection	
<ul style="list-style-type: none"> • for network components or terminal equipment • for signaling contact • for power supply 	<p>RJ45 port</p> <p>2-pole terminal block</p> <p>4-pole terminal block</p>
Number of optical interfaces	
<ul style="list-style-type: none"> • for fiber optic cable / at 100 Mbit/s 	1
Design of the optical interface	
<ul style="list-style-type: none"> • for fiber optic cable / at 100 Mbit/s 	BFOC-Port (Multimode up to 5 km)

Connectable optical power relative to 1 mW	
<ul style="list-style-type: none"> • of the transmitter output / minimum 	-19 dB
<ul style="list-style-type: none"> • of the transmitter output / maximum 	-14 dB
<ul style="list-style-type: none"> • of the receiver input / maximum 	-14 dB
Optical sensitivity relating to 1 mW / of the receiver input / minimum	-31 dB
Damping ratio / of the FOC transmission link / minimum necessary	0 dB
Range / at the optical interface / depending on the optical fiber used	0 ... 5 km

Signal inputs/outputs

Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / Rated value 	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / maximum 	0.1 A

Supply voltage, current consumption, power loss

Supply voltage	
<ul style="list-style-type: none"> • external 	24 V
<ul style="list-style-type: none"> • external 	18 ... 32 V
Type of voltage / of the supply voltage	DC
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.5 A / 60 V
Consumed current	
<ul style="list-style-type: none"> • maximum 	0.12 A
Power loss [W]	
<ul style="list-style-type: none"> • at DC / at 24 V 	3 W

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-10 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +80 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP30
Design	Compact
Width	40 mm
Height	125 mm
Depth	124 mm
Net weight	0.55 kg
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	Yes

- wall mounting

Yes

Product functions / redundancy

Product function

- Parallel Redundancy Protocol (PRP)/operation in the PRP-network
- Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)

No

No

Standards, specifications, approvals

Standard

- for FM
- for hazardous zone
- for safety / from CSA and UL
- for hazardous zone / from CSA and UL
- for emitted interference
- for interference immunity

FM3611: Class 1, Divison 2, Group A, B, C, D / T.., Class 1, Zone 2, Group IIC, T..
 EN 600079-15 II 3 G EEx nA II T.. KEMA 06 ATEX 0021 X
 UL 60950-1, CSA C22.2 No. 60950-1
 UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T..
 EN 61000-6-3
 EN 61000-6-4:2001

Certificate of suitability

- CE marking
- C-Tick
- KC approval

EN 61000-6-2:2001, EN 61000-6-4:2001
 Yes
 Yes
 Yes

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)
- Bureau Veritas (BV)
- Det Norske Veritas (DNV)
- Germanische Lloyd (GL)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (NK)
- Polski Rejestr Statkow (PRS)

Yes
 Yes
 Yes
 Yes
 Yes
 Yes
 No

MTBF

134 y

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/11/2019