

SIDOOR NT40 Switched-mode power supply, Input voltage: 230V AC (+-15%), 50/60 Hz, Output voltage: 36VDC, IP54, incl. line cable with Safety plug (CEE 7/4) of the Length 2 m, incl. connecting cable to Control device of length 1.5 m, -20 to +55 °C



Figure similar

General information

Product type designation	NT40
--------------------------	------

Installation type/mounting

Mounting type	Four 5 mm screws
---------------	------------------

Supply voltage

Rated value (AC)	230 V
------------------	-------

relative symmetrical tolerance of the supply voltage	15 %
--	------

Line frequency

• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz

Input current

Current consumption for 2 s, max.	3.5 A
-----------------------------------	-------

Rated value at 230 V AC	0.7 A
-------------------------	-------

Operational current of fuse protection at input, min.	6 A
---	-----

Operational current of fuse protection at input, max.	10 A
---	------

Tripping characteristic class of fuse protection at input	B
Output voltage	
Rated value (DC)	36 V; SELV
Relative symmetrical tolerance of the output voltage	3 %
Output current	
Current output (rated value)	2.5 A
Temporary overload current (for 2 s maximum)	15 A
Power	
Active power input, max.	100 W
Emitted active power, max.	100 W
Emitted active power (restricted to 2 s)	540 W
Efficiency at 230 V AC (with 100 W emitted active power)	90 %
Active apparent power, max.	650 V·A
Isolation	
Overvoltage category	2
Degree and class of protection	
IP degree of protection	IP54
Equipment protection class	I
Standards, approvals, certificates	
CE mark	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
China RoHS compliance	Yes
Standard for EMC	EMC Directive 2004/108/EC, EN 12015, EN 12016
Standard for safety	EN 60950-1
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C
• max.	55 °C
• Remark	No direct exposure to the sun
Ambient temperature during storage/transportation	
• Storage, min.	-20 °C
• Storage, max.	70 °C
• Transportation, min.	-40 °C
• Transportation, max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	

• No condensation, min.	10 %
• No condensation, max.	93 %

Cables	
Cable length	
• Input side	2 m
• Output side	1.5 m

Connection method	
Design of electrical connection at input	SCHUKO connector DIN 49.441, CEE7/VII
Design of electrical connection at output	WAGO 721-103/026

Dimensions	
Width	270 mm
Height	55 mm
Depth	80 mm

last modified: 11/25/2019