

Connection box PN plus for Mobile Panels (PROFINET)



Figure similar

General information	
Product function	
• Location identifier	Yes
FH technology	
Safety evaluation through direct wiring	
• Reconnection without emergency stop circuit interruption	Yes
• Monitoring the STOP button	Yes
Supply voltage	
Type of supply voltage	24 V DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.5 A
Power	
Active power input, typ.	12 W

Interfaces	
Interfaces/bus type	Ethernet
Connection point identification	Yes
Industrial Ethernet	
<ul style="list-style-type: none"> Industrial Ethernet interface 	2x Fast Ethernet
<ul style="list-style-type: none"> Industrial Ethernet status LED 	6
Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No
Use in hazardous areas	
<ul style="list-style-type: none"> ATEX Zone 2 	No
<ul style="list-style-type: none"> ATEX Zone 22 	No
<ul style="list-style-type: none"> FM Class I Division 2 	No
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> Operation (vertical installation) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. 	0 to +50 °C 0 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-20 °C 70 °C
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	85 %
Dimensions	
Width	230 mm
Height	120 mm
Depth	80 mm
Weights	
Weight (without packaging)	0.5 kg
Other	
free hotline	Yes
Usable in the following products	
<ul style="list-style-type: none"> Product 1 	6AV6645-0BA01-0AX0

- Product 2
- Product 3
- Product 4
- Product 5

[6AV6645-0BB01-0AX0](#)

[6AV6645-0BC01-0AX0](#)

[6AV6645-0BE02-0AX0](#)

6AV6645-0C*

last modified:

08/16/2019