

### Product type designation

### RF350M mobile hand-held terminal

SIMATIC RF300 handheld terminal RF350M; RF300, ISO 15693 and MOBY E; Basic unit Nordic ID Merlin; with integrated RFID read/write unit and user software; Windows CE operating system; with battery; without charging/docking station



Suitability for operation	RF300, RF200/ISO 15693 and MOBY E transponder
Range	80 mm
<b>Radio frequencies</b>	
Operating frequency / Rated value	13.56 MHz
<b>Electrical data</b>	
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	No
<b>Supply voltage, current consumption, power loss</b>	
Type of current supply	Battery operation or mains operation via docking station
Type of battery	Lithium ion accumulator, fast charging capability
Type of battery / as back-up battery / Integrated	Lithium ion battery, permanently installed, cannot be replaced by customer
Battery capacity	2.6 A·h
Operating period / with standard battery / typical	8 h
<b>Ambient conditions</b>	
Ambient temperature	
• during operation	-20 ... +55 °C

• during storage	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Height of fall / maximum	1.2 m
Protection class IP	IP54

### Design, dimensions and weight

Width	90 mm
Height	250 mm
Depth	47 mm
Net weight	0.6 kg

### Product features, product functions, product components / general

Design of the display	QVGA color touch screen 3.5 inch, 240 x 320 pixels
Operator element version	Alphanumeric
Design of acoustic signaling element	Speakers
Design of the interface	WLAN, USB and Ethernet via charging station
Storage capacity	
• of the RAM	256 Mibyte
• of the data and program memory	288 Mibyte
• of the data memory / can be used	256 Mibyte

### Product functions / management, configuration, engineering

Operating system / pre-installed	Windows Embedded CE 6.0
----------------------------------	-------------------------

### Standards, specifications, approvals

Certificate of suitability	EMC: EN 55022, EN 301 489, EN 300 330, EN 300 328, EN 301 893, safety: EN 60950
----------------------------	---

### accessories

accessories	Charging/docking station with USB- and Ethernet interface, changeable accumulator Li-ion 2600 mAh / 7,4 V
-------------	---

### Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a>
• to website: Industrial communication	<a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx Download Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**last modified:** 12/14/2019