

SIMATIC S7-1200, Digital I/O SB 1223, 2 DI/2 DQ, 5V DC 200kHz



Figure similar

General information	
Product type designation	SB 1223, DI 2x5 V DC/DQ 2x5 V DC 200 kHz
Input current	
from backplane bus 5 V DC, typ.	35 mA
Power loss	
Power loss, typ.	0.5 W
Digital inputs	
Number of digital inputs	2; Current-sourcing
• in groups of	2
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	5 V
• for signal "0"	(L+ minus 1.0 V DC) ... L+
• for signal "1"	0 V ... (L+ minus 2.0 V DC)
Input current	

<ul style="list-style-type: none"> <li>• for signal "0", max. (permissible quiescent current)</li> </ul>	2.2 mA
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	5.1 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 $\mu$ s; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	50 m; shielded, twisted pair
<b>Digital outputs</b>	
Number of digital outputs	2; MOSFET, solid-state (current-sinking/current-sourcing)
<ul style="list-style-type: none"> <li>• in groups of</li> </ul>	2
Short-circuit protection	No
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	0.1 A
<b>Load resistance range</b>	
<ul style="list-style-type: none"> <li>• upper limit</li> </ul>	7 $\Omega$
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>	5 V
<ul style="list-style-type: none"> <li>• for signal "0", max.</li> </ul>	0.2 V
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ minus 0.7 V DC
<ul style="list-style-type: none"> <li>• for signal "1", max.</li> </ul>	6 V
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul>	0.1 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	50 m
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• for status of the inputs</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for status of the outputs</li> </ul>	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes

KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
<b>Free fall</b>	
• Fall height, max.	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
• min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
<b>Relative humidity</b>	
• Operation at 25 °C without condensation, max.	95 %
<b>Mechanics/material</b>	
<b>Enclosure material (front)</b>	
• Plastic	Yes
<b>Dimensions</b>	
Width	38 mm
Height	62 mm
Depth	21 mm
<b>Weights</b>	
Weight, approx.	35 g
<b>last modified:</b>	08/15/2019