

POWER SUPPLY PS307 24 V/5 A
 SIMATIC S7-300 Regulated power supply PS307 input: 120/230 V
 AC, output: 24 V/5 A DC



| Input | |
|--|---|
| Input | 1-phase AC |
| Supply voltage | |
| <ul style="list-style-type: none"> • 1 at AC Rated value • 2 at AC Rated value • Note | 120 V 230 V Automatic range selection |
| Input voltage | |
| <ul style="list-style-type: none"> • 1 at AC • 2 at AC | 85 ... 132 V 170 ... 264 V |
| Wide-range input | No |
| Overvoltage resistance | 2.3 × Vin rated, 1.3 ms |
| Mains buffering at lout rated, min. | 20 ms; at Vin = 93/187 V |
| Rated line frequency 1 | 50 Hz |
| Rated line frequency 2 | 60 Hz |
| Rated line range | 47 ... 63 Hz |
| Input current | |
| <ul style="list-style-type: none"> • at rated input voltage 120 V • at rated input voltage 230 V | 2.3 A 1.2 A |
| Switch-on current limiting (+25 °C), max. | 20 A |

| | |
|---|--|
| Duration of inrush current limiting at 25 °C | |
| • maximum | 3 ms |
| I ² t, max. | 1.2 A ² ·s |
| Built-in incoming fuse | T 3,15 A/250 V (not accessible) |
| Protection in the mains power input (IEC 898) | Recommended miniature circuit breaker: from 6 A characteristic C |

Output

| | |
|---|---|
| Output | Controlled, isolated DC voltage |
| Rated voltage V _{out} DC | 24 V |
| Total tolerance, static ± | 3 % |
| Static mains compensation, approx. | 0.1 % |
| Static load balancing, approx. | 0.5 % |
| Residual ripple peak-peak, max. | 50 mV |
| Residual ripple peak-peak, typ. | 10 mV |
| Spikes peak-peak, max. (bandwidth: 20 MHz) | 150 mV |
| Spikes peak-peak, typ. (bandwidth: 20 MHz) | 20 mV |
| Product function Output voltage adjustable | No |
| Output voltage setting | - |
| Status display | Green LED for 24 V OK |
| On/off behavior | No overshoot of V _{out} (soft start) |
| Startup delay, max. | 2 s |
| Voltage rise, typ. | 10 ms |
| Rated current value I _{out} rated | 5 A |
| Current range | 0 ... 5 A |
| Supplied active power typical | 120 W |
| Short-term overload current | |
| • on short-circuiting during the start-up typical | 20 A |
| • at short-circuit during operation typical | 20 A |
| Duration of overloading capability for excess current | |
| • on short-circuiting during the start-up | 100 ms |
| • at short-circuit during operation | 100 ms |
| Parallel switching for enhanced performance | Yes |

Efficiency

| | |
|---|------|
| Efficiency at V _{out} rated, I _{out} rated, approx. | 87 % |
| Power loss at V _{out} rated, I _{out} rated, approx. | 18 W |

Closed-loop control

| | |
|--|--------|
| Dynamic mains compensation (V _{in} rated ±15 %), max. | 0.1 % |
| Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ. | 1 % |
| Load step setting time 50 to 100%, typ. | 0.3 ms |
| Load step setting time 100 to 50%, typ. | 0.3 ms |

Protection and monitoring

| | |
|--|--|
| Output overvoltage protection | Additional control loop, shutdown at < 28.8 V, automatic restart |
| Current limitation | 5.5 ... 6.5 A |
| Property of the output Short-circuit proof | Yes |
| Short-circuit protection | Electronic shutdown, automatic restart |
| Enduring short circuit current RMS value <ul style="list-style-type: none"> • maximum | 7 A |

Safety

| | |
|--|--|
| Primary/secondary isolation | Yes |
| Galvanic isolation | Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178 |
| Protection class | Class I |
| Leakage current <ul style="list-style-type: none"> • maximum • typical | 3.5 mA 0.5 mA |
| CE mark | Yes |
| UL/cUL (CSA) approval | cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289 |
| Explosion protection | ATEX (EX) II 3G Ex nA II T4; cULus (ANSI/ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455 |
| FM approval | Class I, Div. 2, Group ABCD, T4 |
| CB approval | No |
| Marine approval | In S7-300 system |
| Degree of protection (EN 60529) | IP20 |

EMC

| | |
|-----------------------------|------------------|
| Emitted interference | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2 |
| Noise immunity | EN 61000-6-2 |

Operating data

| | |
|--|--|
| Ambient temperature <ul style="list-style-type: none"> • during operation — Note • during transport • during storage | 0 ... 60 °C with natural convection -40 ... +85 °C -40 ... +85 °C |
| Humidity class according to EN 60721 | Climate class 3K3, no condensation |

Mechanics

| | |
|---|---|
| Connection technology | screw-type terminals |
| Connections <ul style="list-style-type: none"> • Supply input • Output • Auxiliary | L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded L+, M: 3 screw terminals each for 0.5 ... 2.5 mm ² - |
| Width of the enclosure | 60 mm |
| Height of the enclosure | 125 mm |

| | |
|--|---|
| Depth of the enclosure | 120 mm |
| Required spacing | |
| • top | 40 mm |
| • bottom | 40 mm |
| • left | 0 mm |
| • right | 0 mm |
| Weight, approx. | 0.6 kg |
| Product feature of the enclosure housing for side-by-side mounting | Yes |
| Installation | Can be mounted onto S7 rail |
| Mechanical accessories | Mounting adapter for standard mounting rail (6EP1971-1BA00) |
| MTBF at 40 °C | 2 480 589 h |
| Other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |