SIEMENS

Data sheet

6GK5004-1BD00-1AB2

SCALANCE XB004-1 unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 4x 10/100 Mbit/s twisted pair ports with RJ45 sockets; 1 x 100 Mbit/s multimode glass FOC port with SC socket; Manual available as a download

Product type designation	SCALANCE XB004-1	
Transfer rate		
Transfer rate	10 Mbit/s, 100 Mbit/s	
Interfaces / for communication / Integrated		
Number of electrical connections		
 for network components or terminal equipment 	4; RJ45	
Number of 100 Mbit/s SC ports		
• for multimode	1	
Interfaces / other		
Number of electrical connections		
• for power supply	1	
Type of electrical connection		
• for power supply	3-pole terminal block	
Supply voltage, current consumption, power loss		
Type of voltage / of the supply voltage	AC/DC	
Supply voltage		
• external	24 V	

• external / minimum	19.2 V
• external / maximum	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.11 A
Power loss [W]	
• at DC / at 24 V	2.64 W
Ambient conditions Ambient temperature	
	-10 +60 °C
during operation	-40 +80 °C
• during storage	
during transport	-40 +80 °C
Relative humidity	
• at 25 °C / without condensation / during	95 %
operation / maximum Protection class IP	IP20
	IF 20
Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.165 kg
Mounting type	
 35 mm DIN rail mounting 	Yes
● wall mounting	Yes
 S7-1500 rail mounting 	No
Product functions / management, configuration, en	gineering
Product function	
multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No
Product functions / redundancy	
Product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No
Standards, specifications, approvals	
Standard	

• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
 for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
 for emitted interference 	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
MTBF	232 у

Standards,	specifications,	approvals / CE	
Certificate	of suitability / CF	marking	

EN 61000-6-2, EN 61000-6-4
Yes
Yes

Yes

Internet-Link	
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
 to website: Industrial communication 	http://www.siemens.com/simatic-net
 to website: Industry Mall 	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx Download Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

02/12/2020