

SIMATIC ET 200SP, Analog input module, AI 8xRTD/TC 2-wire High Feature suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%



General information	
Product type designation	AI 8xRTD/TC 2-wire HF, PU 1
HW functional status	From FS05
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Measuring range scalable	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V14 / -
• STEP 7 configurable/integrated as of version	V5.6
• PROFIBUS as of GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET as of GSD version/GSD revision	GSDML V2.3
Operating mode	
• Oversampling	No

- MSI

No

### CiR – Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

### Input current

Current consumption, max.	35 mA
---------------------------	-------

### Power loss

Power loss, typ.	0.75 W
------------------	--------

### Address area

#### Address space per module

- Address space per module, max. 16 byte; + 1 byte for QI information

### Hardware configuration

Automatic encoding	Yes
--------------------	-----

- Mechanical coding element Yes

#### Selection of BaseUnit for connection variants

- 2-wire connection BU type A0, A1

### Analog inputs

Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	30 V
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels)
Technical unit for temperature measurement adjustable	Yes; °C/°F/K

#### Input ranges (rated values), voltages

- -1 V to +1 V Yes; 16 bit incl. sign
- Input resistance (-1 V to +1 V) 1 MΩ
- -250 mV to +250 mV Yes; 16 bit incl. sign
- Input resistance (-250 mV to +250 mV) 1 MΩ
- -50 mV to +50 mV Yes; 16 bit incl. sign
- Input resistance (-50 mV to +50 mV) 1 MΩ
- -80 mV to +80 mV Yes; 16 bit incl. sign
- Input resistance (-80 mV to +80 mV) 1 MΩ

#### Input ranges (rated values), thermocouples

- Type B Yes; 16 bit incl. sign

- Input resistance (Type B) 1 MΩ
- Type C Yes; 16 bit incl. sign
- Input resistance (Type C) 1 MΩ
- Type E Yes; 16 bit incl. sign
- Input resistance (Type E) 1 MΩ
- Type J Yes; 16 bit incl. sign
- Input resistance (type J) 1 MΩ
- Type K Yes; 16 bit incl. sign
- Input resistance (Type K) 1 MΩ
- Type L Yes; 16 bit incl. sign
- Input resistance (Type L) 1 MΩ
- Type N Yes; 16 bit incl. sign
- Input resistance (Type N) 1 MΩ
- Type R Yes; 16 bit incl. sign
- Input resistance (Type R) 1 MΩ
- Type S Yes; 16 bit incl. sign
- Input resistance (Type S) 1 MΩ
- Type T Yes; 16 bit incl. sign
- Input resistance (Type T) 1 MΩ
- Type U Yes; 16 bit incl. sign
- Input resistance (Type U) 1 MΩ
- Type TXK/TXK(L) to GOST Yes; 16 bit incl. sign
- Input resistance (Type TXK/TXK(L) to GOST) 1 MΩ

**Input ranges (rated values), resistance thermometer**

- Ni 100 Yes; 16 bit incl. sign
- Input resistance (Ni 100) 1 MΩ
- Ni 1000 Yes; 16 bit incl. sign
- Input resistance (Ni 1000) 1 MΩ
- LG-Ni 1000 Yes; 16 bit incl. sign
- Input resistance (LG-Ni 1000) 1 MΩ
- Ni 120 Yes; 16 bit incl. sign
- Input resistance (Ni 120) 1 MΩ
- Ni 200 Yes; 16 bit incl. sign
- Input resistance (Ni 200) 1 MΩ
- Ni 500 Yes; 16 bit incl. sign
- Input resistance (Ni 500) 1 MΩ
- Pt 100 Yes; 16 bit incl. sign
- Input resistance (Pt 100) 1 MΩ
- Pt 1000 Yes; 16 bit incl. sign
- Input resistance (Pt 1000) 1 MΩ
- Pt 200 Yes; 16 bit incl. sign

• Input resistance (Pt 200)	1 MΩ
• Pt 500	Yes; 16 bit incl. sign
• Input resistance (Pt 500)	1 MΩ
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	Yes; 15 bit
• Input resistance (0 to 150 ohms)	1 MΩ
• 0 to 300 ohms	Yes; 15 bit
• Input resistance (0 to 300 ohms)	1 MΩ
• 0 to 600 ohms	Yes; 15 bit
• Input resistance (0 to 600 ohms)	1 MΩ
• 0 to 3000 ohms	Yes; 15 bit
• Input resistance (0 to 3000 ohms)	1 MΩ
• 0 to 6000 ohms	Yes; 15 bit
• Input resistance (0 to 6000 ohms)	1 MΩ
• PTC	Yes; 15 bit
• Input resistance (PTC)	1 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
<b>Cable length</b>	
• shielded, max.	200 m; 50 m with thermocouples
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
• Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz
• Conversion time (per channel)	180 / 60 / 50 ms
<b>Smoothing of measured values</b>	
• Number of smoothing levels	4; None; 4/8/16 times
• parameterizable	Yes

## Encoder

Connection of signal encoders	
• for voltage measurement	Yes
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	No
• for resistance measurement with four-wire connection	No

## Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.1 %
• Resistance, relative to input range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.05 %
• Resistance, relative to input range, (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
• Common mode voltage, max.	10 V
• Common mode interference, min.	90 dB

## Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
---	----

## Interrupts/diagnostics/status information

Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; channel by channel
• Group error	Yes
• Overflow/underflow	Yes; channel by channel
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; Green PWR LED

- Channel status display
- for channel diagnostics
- for module diagnostics

Yes; Green LED  
 Yes; Red LED  
 Yes; green/red DIAG LED

### Potential separation

#### Potential separation channels

- between the channels
- between the channels and backplane bus
- between the channels and the power supply of the electronics

No  
 Yes  
 Yes

### Isolation

Isolation tested with 707 V DC (type test)

### Ambient conditions

#### Ambient temperature during operation

- horizontal installation, min.
- horizontal installation, max.
- vertical installation, min.
- vertical installation, max.

-30 °C  
 60 °C  
 -30 °C  
 50 °C

#### Altitude during operation relating to sea level

- Installation altitude above sea level, max.

5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

### Dimensions

Width 15 mm  
 Height 73 mm  
 Depth 58 mm

**last modified:** 11/25/2019