



Figure similar

MLFB-Ordering data

6SL3210-5FE13-5UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data	Ambient conditions
------------	--------------------

<b>Input</b>	
Number of phases	3 AC
Line voltage	380 ... 480 V +10 % -15 %
Line frequency	45 ... 66 Hz

Cooling	Fan
Installation altitude	1000 m

<b>Output</b>	
Rated power	3.50 kW
Rated current (IN)	11.00 A
Max. output current	33.00 A

<b>Ambient temperature</b>	
Operation	0 ... 45 °C
Storage	-40 ... 70 °C

<b>Relative humidity</b>	
Max. operation	90 %

Inputs / outputs
------------------

Standards
-----------

<b>Standard digital inputs</b>	
Number	10

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------

<b>Digital outputs</b>	
Number	6

<b>Analog inputs</b>	
Number	2

<b>Analog outputs</b>	
Number	2

Mechanical data
-----------------

Degree of protection	IP20 / UL open type
Size	FSC
Net weight	5.65 kg
Width	140.0 mm
Height	260.0 mm
Depth	240.0 mm