

SIMATIC DP, ET 200ECO PN, 4 AO U/I; 4xM12, Degree of protection IP67



General information

Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H

Supply voltage

Rated value (DC)	24 V
Reverse polarity protection	Yes

Input current

Current consumption, typ.	280 mA
---------------------------	--------

Actuator supply

Number of outputs	4
Short-circuit protection	Yes; Electronic at 1.4 A

Output current

<ul style="list-style-type: none"> Rated value 	1 A; Maximum
---	--------------

Power loss

Power loss, typ.	5.5 W
------------------	-------

Analog outputs

Number of analog outputs	4
--------------------------	---

Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	30 mA
Current output, no-load voltage, max.	20 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 k Ω
• with voltage outputs, capacitive load, max.	1 μ F
• with current outputs, max.	600 Ω
• with current outputs, inductive load, max.	1 mH
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs towards MANA	28.8 V permanent, 35 V for max. 500 ms
Cable length	
• shielded, max.	30 m
Analog value generation for the outputs	
Analog value display	SIMATIC S7 format
Conversion principle	Resistor network
Integration and conversion time/resolution per channel	
• Resolution (incl. overrange)	15 bit + sign
• Conversion time (per channel)	1 ms
Settling time	
• for resistive load	2 ms
• for capacitive load	1.8 ms
• for inductive load	2 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	U: \pm 0.6 mVrms; I: \pm 0.4 nArms
Linearity error (relative to output range), (+/-)	0.02 %
Temperature error (relative to output range), (+/-)	U: 0.001%/°C; I: 0.0025%/°C
Crosstalk between the outputs, min.	70 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.008 %

Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1

1. Interface

Interface types	
• integrated switch	Yes
• M12 port	Yes

Interface types

M12 port	
• Transmission procedure	100BASE-TX
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s

Protocols

Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No

PROFINET IO Device

Services	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes

Open IE communication

• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes

Interrupts/diagnostics/status information

Diagnostics function	Yes
Substitute values connectable	Yes

Alarms

• Diagnostic alarm	Yes
--------------------	-----

Diagnostic messages

• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; Green "ON" LED
• Wire-break	Yes; Channel-by-channel with current output
• Short-circuit	Yes; Channel-by-channel with voltage output
• Group error	Yes; Red/yellow "SF/MT" LED

Potential separation

between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Potential separation channels	
• between the channels	No

Permissible potential difference	
between M internally and the outputs	10 Vpp AC

Isolation	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3

Degree and class of protection	
IP degree of protection	IP65/67

Connection method	
Design of electrical connection	4/5-pin M12 circular connectors

Dimensions	
Width	60 mm
Height	175 mm
Depth	49 mm

Weights	
Weight, approx.	930 g
last modified:	11/16/2019