



Figure similar

MLFB-Ordering data 6SL3040-1MA00-0AA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Inputs / outputs

Digital inputs

Number of potential-free inputs	12
Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	3.5 mA
Delay time L→H, typ.	50 μs
Delay time H→L, typ.	150 μs

Digital I/O

Number of bidirectional, not potential-free inputs 8

As input

Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	3.5 mA
Delay time L→H	5 μs
Delay time H→L	50 μs

As output

Voltage	DC 24 V
Load current per digital output, max.	500 mA
Delay time L→H, typ./ max.	150 μs / 400 μs
Delay time H→L, typ./ max.	75 μs / 100 μs



Figure similar

MLFB-Ordering data

6SL3040-1MA00-0AA0

Electrical data

Electronics power supply	DC 24 V (20,4 ... 28,8 V)
Max. power consumption ²⁾	1.00 A
Power loss, max.	24 W

Mechanical data

Dimensions

Width	50 mm (1.97 in)
Height	300 mm (11.81 in)
Depth	226 mm (8.90 in)
Net weight	2.20 kg (4.85 lb)

Ambient conditions

Installation altitude	2000 m (6561.68 ft)
-----------------------	---------------------

Ambient temperature during

Operation	0 ... 55 °C (32 ... 131 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Transport, max.	95 % at 40 °C (104 °F)
-----------------	---------------------------

Connections

PE connection	1 (M5 screw)
DRIVE-CLiQ	4
PROFINET	--
PROFIBUS	1
RS232	1
Ethernet	1
Temperature sensor	--
24 V	1
Measuring sockets	3

Number of slots

Flash card	1
for option modules	1

Communication

Communication	Profibus DP
---------------	-------------

Standards

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------

²⁾ without taking into account digital outputs. Option slot extension and DRIVE-CLiQ supply