## **SIEMENS**

## Data sheet

6AV6671-8XE00-0AX0

Converter RS422 to RS232 Converter RS422 to RS232, can be screwed together with RS422 interface, Cable outlet 180 degrees, for connection of third-party PLC



| General information                            |                                    |  |
|--|------------------------------------|--|
| Product type designation                       | Converter, RS 422 to RS 232        |  |
| Installation type/mounting                     |                                    |  |
|  | Vac. Can be carrying onto the LIMI |  |
| Wall mounting/direct mounting                  | Yes; Can be screwed onto the HMI   |  |
| Interfaces                                     |                                    |  |
| HMI-side interface                             |                                    |  |
| <ul> <li>Number of pins HMI-side</li> </ul>    | 9; Male (RS 422)                   |  |
| Device-side interface                          |                                    |  |
| <ul> <li>Number of pins device-side</li> </ul> | 9; Female (RS 232)                 |  |
|  |                                    |  |
| Degree and class of protection                 |                                    |  |
| IP (all-round)                                 | none                               |  |
| Standards, approvals, certificates             |                                    |  |
| CE mark  | Yes                                |  |
| RoHS conformity                                | Yes                                |  |
| China RoHS compliance                          | Yes                                |  |
| Ambient conditions                             |                                    |  |
| Ambient temperature during operation           |                                    |  |

| • min.   | 0 °C   |
|--|--|
| • max.   | 55 °C  |
| Ambient temperature during storage/transportation  |  |
| • min.   | -20 °C   |
| • max.   | 70 °C  |
| Relative humidity                                  |  |
| Operation, max.                                    | 95 %   |
| Mechanics/material                                 |  |
| Enclosure material (front)                         |  |
| Plastic  | Yes  |
| Screw type   |  |
| • 4.5 V  | Yes; HMI page  |
| Torques/forces                                     |  |
| Tightening torque, min.                            | 0.18 N·m; Insufficient torque can lead to loosening of the screws  |
| <ul> <li>Tightening torque, max.</li> </ul>        | 0.2 N·m  |
| <ul> <li>Tightening torque, recommended</li> </ul> | 0.2 N·m; Higher torques may damage the product   |
| Dimensions   |  |
| Width  | 31 mm  |
| Height   | 50 mm  |
| Thickness  | 11 mm  |
| Weights  |  |
| Weight without packaging                           | 26 g   |
| Scope of supply                                    |  |
| Delivery quantity in pieces                        | 1  |
| Other  |  |
| Merchandise  | No   |
| Manufacturer name                                  | SIEMENS AG   |
| Manufacturer's address                             | Gleiwitzerstraße 555, 90475 Nuremberg, Germany   |
| Target devices                                     | suitable for all SIMATIC HMI RS 422 interfaces, for details refer to the operating instructions of the respective device |
| Usable in the following products                   |  |
| • Product 1  | 6AV6642-0*   |
| • Product 2  | 6AV6542-0*   |
| • Product 3  | 6AV6545-0*   |
| • Product 4  | 6AV6644-*  |
| • Product 5  | 6AV6545-8*   |
| • Product 6  | 6AV6640-0C*  |
| • Product 7  | 6AV6643-7BA00-*  |
| • Product 8  | 6AV6643-7CD00-*  |
| • Product 9  | 6AV6643-7DD00-*  |
|  |  |

| Product 10   | 6av2124-0* |
|--------------|------------|
| • Product 11 | 6AV2124-1* |
| • Product 12 | 6AV2124-2* |
| • Product 13 | 6AV6647-0* |
| • Product 14 | 6AV6643-8* |
| • Product 15 | 6AV2123-2* |

**last modified:** 08/15/2019