

TWISTED RIBBON CBL 16X0,14,L=30M,SHIELD.
 Flat ribbon cable with 16 cores 0.14 mm², Length = 30 m shielded



Target system	SIMATIC S7-300 / 1500
Suitability for use	Digital and analog I/O modules
Product type designation	Fully modular connection
Product designation	Round-sheath ribbon cable

Operating data	
Operating voltage / at DC	
<ul style="list-style-type: none"> Rated value maximum 	24 V 60 V
Ambient temperature	
<ul style="list-style-type: none"> during operation during storage 	0 ... 60 °C -30 ... +70 °C

General data	
Suitability for interaction	
<ul style="list-style-type: none"> Input card PLC PLC output card 	Yes Yes
Suitability for use	
<ul style="list-style-type: none"> digital signal transmission analog signal transmission 	Yes Yes

Product properties, functions, components / general

Number of channels	8
Design of cable	Round-sheath ribbon cable
Wire length	30 m
Number of poles	16
Number of conductors / of connecting cable	16
Conductor cross section / Rated value	0.14 mm ²
Color / of cable sheath	Black
Outer diameter / of cable sheath	10.5 mm
Material / of the connecting cable sheath	PVC
Marking / of cores	Coded wire
Design of the shield	braided shield
Type of electrical connection / on enclosure	other
Type of electrical connection / in the field	other
Certificate of suitability / cULus approval	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	4.4 kg
last modified:	10/15/2019