

CONNECTING CABLE S7 SHIELDED 2.0M
 Connecting cable shielded for SIMATIC S7-300/1500 between front connector module and Connection module 16x0.14 mm² with IDC connectors, Length = 2.0 m



Figure similar

Target system	SIMATIC S7-300 / 1500
Suitability for use	Digital and analog I/O modules
Product type designation	Fully modular connection
Product designation	Pre-assembled round cable

Operating data	
Operating voltage / at DC	
<ul style="list-style-type: none"> • Rated value • maximum 	24 V 60 V
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	0 ... 60 °C -30 ... +70 °C

General data	
Suitability for interaction	
<ul style="list-style-type: none"> • Input card PLC • PLC output card 	Yes Yes
Suitability for use	
<ul style="list-style-type: none"> • digital signal transmission 	Yes

- analog signal transmission

Yes

Product properties, functions, components / general

Number of channels	8
Design of cable	Round cable
Wire length	2 m
Number of poles	16
Number of conductors / of connecting cable	16
Conductor cross section / Rated value	0.14 mm ²
Color / of cable sheath	Black
Outer diameter / of cable sheath	7 mm
Material / of the connecting cable sheath	PVC
Design of the shield	braided shield
Connector type	IDC connector
Type of electrical connection / on enclosure	Connector strip
Number of poles / at the 1st interface	16; cable side front connector module
Type of electrical connection / in the field	Connector strip
Number of poles / at the 2nd interface	16; on the connection module
Certificate of suitability / cULus approval	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	0.19 kg
last modified:	10/15/2019