SIEMENS

Data sheet

6GK1907-0DB10-6AA3

Product type designation Product description

Power M12 Plug PRO

M12 power connector, 4-pole, A-coded IE Power M12 Cable Connector PRO; plug-in connector for connection to power supply PS791-1PRO for 24 V DC power supply with installation instructions, 4-pole, A-coded, 3 units



Suitability for use For connection to PS791-1PRO power supply for 24 V DC voltage supply

Interfaces	
Number of electrical connections	
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Integrated screw contacts for 2-core power cables
• for network components or terminal equipment	M12 connector (male insert, A-coded, 4-pin)
Type of electrical connection / FastConnect	No

Mechanical data		
Material / of the enclosure	plastic	
Locking mechanism design	Screw	
Type of cable outlet	180° cable outlet	
Width	19 mm	
Height	19 mm	
Depth	73 mm	
Net weight	40 g	

Ambient conditions	
Ambient temperature	
during operation	-40 +70 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
Chemical resistance	
● to water	resistant
Protection class IP	IP65/67

Product features, product functions, product components / general	
Product feature	
• silicon-free	Yes
Product component	
• strain relief	Yes

Standards, specifications, approvals Certificate of suitability RoHS conformity UL approval Railway application in accordance with EN 50155

Further information / Internet-Links

• to website: Industry Online Support

Internet-	

to website: Selector SIMATIC NET
 SELECTION TOOL
 to website: Industrial communication
 to website: Industry Mall
 http://www.siemens.com/simatic-net
 https://mall.industry.siemens.com

to website: Industry Mail
 to website: Information and Download Center
 to website: Image database
 to website: CAx Download Manager
 http://www.siemens.com/bilddb
 http://www.siemens.com/cax

last modified: 11/16/2019

https://support.industry.siemens.com