

SIMATIC S7-300, Front connector with screw contacts, 40-pole



General information

Product type designation	Front connector
--------------------------	-----------------

Ambient conditions

Ambient temperature during operation

- | | |
|--------|-------|
| • min. | 0 °C |
| • max. | 60 °C |

Ambient temperature during storage/transportation

- | | |
|--------|--------|
| • min. | -40 °C |
| • max. | 70 °C |

Accessories

belongs to product	S7-300
--------------------	--------

Connection method

Connection I/O signals

- | | |
|----------------------------------|--|
| • Connection method | Screw terminals |
| • Number of lines per connection | 1; Or 2 cables up to 0.75 mm ² (total) in a shared end sleeve |

Conductor cross-section in mm ²	
--	--

— Connectable cable cross-sections for massive cables, min.	0.25 mm ²
— Connectable cable cross-sections for massive cables, min.	0.75 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, max.	0.75 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, max.	0.75 mm ²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	19
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	19
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	19
Wire end processing	
— Stripped length of cables, min.	6 mm
— Stripped length of cables, max.	6 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Design A, 5 mm to 7 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Design E, up to 6 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
— Tightening torque, min.	0.4 N·m
— Tightening torque, max.	0.7 N·m
Dimensions	
Width	21.6 mm
Height	125 mm
Depth	40.9 mm
Weights	
Weight, approx.	137 g

last modified:

08/14/2019