



Traditional Flush 2X2 FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

2X2 Flush FRPT, One-Piece Units (PT2X2FIT)

Description	Color	Catalog Number
2X2 Poke-Through Non-metallic Cover	Black	PT2X2BL
	Gray	PT2X2GY
	Black	PT2X2IGBL*
	Gray	PT2X2IGGY*



- Pre-wired 20A Style Line® decorator receptacle and (2) Category 5e data jacks
- Painted aluminum flange
- Approved for use in the City of Chicago

Description	Color/Material	Catalog Number
2X2 Poke-Through	Black/Brass	PT2X2BRS3
	Brass Finish/Brass	PT2X2BRS
	Black/Brass	PT2X2IGBRS3*
	Brass Finish/Brass	PT2X2IGBRS*



- Pre-wired 20A Style Line® decorator receptacle and (2) Category 5e data jacks
- Solid brass flange
- Approved for use in the City of Chicago

Note: *Includes pre-wired 20A isolated ground duplex Style Line® receptacle.

2X2 Flush FRPT, Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) 3/4 in. EMT stem with junction box for power and (2) 1/2 in. EMT stems for low voltage.	PT2X2FIT



Specifications:

- 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)
- For 2 1/4 in. to 7 in. floor thickness
- UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area
- Approved for use in the City of Chicago

Service Fittings

Description	Color	Catalog Number
2X2 Service Fitting Non-metallic Cover/ Aluminum Flange	Black	PT2X2SFBL
	Gray	PT2X2SFGY



- Pre-wired 20A Style Line® decorator receptacle and (2) Category 5e data jacks
- Painted aluminum flange

Description	Color/Material	Catalog Number
2X2 Service Fitting Non-metallic Cover/ Brass Flange	Black/Brass	PT2X2SFBR3
	Brass Finish/Brass	PT2X2SFBR



- Pre-wired 20A Style Line® decorator receptacle and (2) Category 5e data jacks
- Solid brass flange

Accessories

Description	Color/Material	Catalog Number
Non-metallic Replacement Covers	Brass Finish	PT2X2CBRS
	Black	PT2X2CBL
	Gray	PT2X2CGY



Description	Color/Material	Catalog Number
Closure Plug Textured aluminum plug seals 3 in. core hole when FRPT is no longer required and is removed. Maintains the floor's 1 – 4 hour fire rating. UL Listed and CSA Certified.	Gray	FRP250



Note: See page P-33 for technical information.