

touch pen system for capacitive or resistive touch screen Pen incl. holder for 22.5 mm, screw on or glue for capacitive and resistive touch screens Further information, Quantity and content: see technical data



Figure similar

General information	
Product type designation	Touch pen system capacitive technology
Control elements	
Frame size/design	
<ul style="list-style-type: none"> <li>• Standard</li> <li>• Exceptional</li> <li>• Ergonomic</li> </ul>	<p>Yes; For industrial applications</p> <p>Yes; Spare caps can be stowed in the pen</p> <p>Yes; With holder</p>
Installation type/mounting	
Mounting type	Wall-mounting bracket can be mounted with mounting disk, 2x M3 screw or adhesive pads
Mounting position	Horizontal
Front mounting	Yes; Also optimized for PRO Extension Unit 22.5 mm opening (from HS01)
Wall mounting/direct mounting	Yes
Degree and class of protection	
IP (at the front)	IP65 (depending on mounting)

Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes
Ambient temperature during operation	
• min.	-40 °C; At temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended.
• max.	80 °C; At temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended.
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	95 %
Mechanics/material	
Material	
• Plastic	Yes; Attachment cord
• Aluminum	Yes; Touch pen, wall-mounting bracket
Dimensions	
Height	150 mm; Length
Thickness	14 mm; Diameter
Enclosure diameter	37 mm; Diameter wall-mounting bracket
Mounting cutout, height	39 mm; Height wall-mounting bracket
Weights	
Weight without packaging	0.13 kg
Weight incl. packaging	0.14 kg
Scope of supply	
Delivery quantity in pieces	1; 1x touch pen with string, wall-mounting bracket, M6 screw, mounting disk, O-ring, adhesive pads, spare caps for touch pen
Other	
Merchandise	Yes; Function depending on touch sensitivity, not suitable for Ceran cooktops, MP377 Daylight, possibly others
Manufacturer name	QUERUM Maschinenbau GmbH
Manufacturer's address	An der Autobahn L8, 91161 Hilpoltstein, Germany
Target devices	For common capacitive and resistive touch systems
Note:	Length of the interconnecting lead 53 cm to 100 cm
Usable in the following products	
• Product 1	<a href="#">6AV2124-0GC13-0AX0</a>
• Product 2	<a href="#">6AV2124-0QC13-0AX0</a>
<b>last modified:</b>	08/27/2019