

**** Spare part *** Does not correspond to the current version of the standard. Transponder V2 f. Mobile Panel 277(F) IWLAN V2
Attention! Not suitable for Mobile Panel 277(F) IWLAN V1!



Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Degree of protection according to NEMA	NEMA 4x, NEMA 12
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Ambient temperature during operation	
• Operation (vertical installation)	0 to +50 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %

Dimensions

Width	172 mm
Height	90 mm
Depth	38.5 mm

Weights

Weight (without packaging)	0.3 kg
----------------------------	--------

Other

Usable in the following products

- Product 1 [6AV6645-0DD01-0AX1](#)
- Product 2 [6AV6645-0DE01-0AX1](#)
- Product 3 [6AV6645-0EB01-0AX1](#)
- Product 4 [6AV6645-0EC01-0AX1](#)
- Product 5 [6AV6645-0FD01-0AX1](#)
- Product 6 [6AV6645-0FE01-0AX1](#)
- Product 7 [6AV6645-0GB01-0AX1](#)
- Product 8 [6AV6645-0GC01-0AX1](#)

last modified:

06/05/2019