

## MOTION CONNECT 500

### MLFB-Ordering data

6FX5002-2CF02-1DA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Electrical data

Design of the sensor

Test voltage, rms Signal conductors

500 V

Rated voltage U0/U in accordance with EN 50395 Power conductors

30 V

### Mechanical data

Type of connection cable engine side

M23 full thread

Type of connection cable converter side

SUB-D

Maximum cable outer diameter

9.2 mm

Smallest bending radius (fixed installation)

60 mm

Smallest bending radius (flexible installation)

100 mm

Number of bends, max.

2,000,000

Maximum traversing velocity

180 m/min

Acceleration horizontal, max

5 m/s<sup>2</sup>

Tensile stress, max. Fixed installation

50 N/mm<sup>2</sup>

Tensile stress, max. Flexible installation

20 N/mm<sup>2</sup>

Torsional stress

Absolute 30°/m

Length

30.0 m



Figure similar

MLFB-Ordering data

6FX5002-2CF02-1DA0

## Technical data

### Ambient temperature

Operation with permanently installed cable	-20 ... 80 °C
Operation with moving cable	0 ... 60 °C
Storage	-20 ... 80 °C
Kind of connection cable	Basis cable
Material of the cable sheath	PVC DESINA-Color green RAL 6018
Type of insulation	Without CFC and silicone
Standard for behavior in fire: flame resistance	EN 60332-1-1 to 1-3
Oil resistance	EN 60811-2-1 (mineral oil only)
Verification of suitability as authorisation for USA	UL758, cURus with AWM-Style
Verification of suitability as authorisation for Canada	CSA-C22.2-N.210.2-M90