

Product type designation

Product description

KEY-PLUG SINEMA RC

Removable medium for activating SINEMA RC for SCALANCE M-800 / S615 and for simple device replacement in the event of a fault
KEY-PLUG SINEMA RC, Removable data storage medium for enabling of the connection to SINEMA Remote Connect for S615 and SCALANCE M for simple device replacement in event of fault and for Recording of configuration data



Suitability for use	Activation of SINEMA RC
Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	<p>-40 ... +75 °C</p> <p>-40 ... +80 °C</p> <p>-40 ... +80 °C</p>
Relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20
Design, dimensions and weight	
Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	

- C-PLUG
- KEY-PLUG

No
Yes

Product properties, functions, components / general

Storage capacity 256 MiByte

Standards, specifications, approvals

Reference code

- according to IEC 81346-2:2018

CFA

Further Information / Internet Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/snst>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

05/15/2019