



Figure similar

MLFB-Ordering data

6SL3210-1PB21-0AL0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data | General tech. specifications |
|------------|------------------------------|
|------------|------------------------------|

Input

| | |
|--------------------|--------------------------|
| Number of phases | 1 AC |
| Line voltage | 200 ... 240 V \pm 10 % |
| Line frequency | 47 ... 63 Hz |
| Rated current (LO) | 24.00 A / 13.90 A |
| Rated current (HO) | 20.90 A / 12.10 A |

Output

| | |
|-------------------------------------|--------------|
| Number of phases | 3 AC |
| Rated voltage | 230 V |
| Rated current (LO) | 10.40 A |
| Rated current (HO) | 7.40 A |
| Max. output current | 15.60 A |
| Rated power IEC 230V (LO) | 2.20 kW |
| Rated power NEC 240V (LO) | 3.00 hp |
| Rated power IEC 230V (HO) | 1.50 kW |
| Rated power NEC 240V (HO) | 2.00 hp |
| Pulse frequency | 4 kHz |
| Output frequency for vector control | 0 ... 200 Hz |
| Output frequency for V/f control | 0 ... 550 Hz |

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

| | |
|---------------------------|---------|
| Power factor λ | 0.85 |
| Offset factor $\cos \phi$ | 0.95 |
| Efficiency η | 0.96 |
| Sound pressure level (1m) | 62 dB |
| Power loss | 0.12 kW |
| Filter class (integrated) | Class A |

Ambient conditions

| | |
|----------------------------|--|
| Cooling | Internal air cooling |
| Cooling air requirement | 0.009 m ³ /s (0.325 ft ³ /s) |
| Installation altitude | 1000 m (3280.84 ft) |
| Ambient temperature | |
| Operation LO | -5 ... 40 °C (23 ... 104 °F) |
| Operation HO | -5 ... 50 °C (23 ... 122 °F) |
| Transport | -25 ... 55 °C (-13 ... 131 °F) |
| Storage | -25 ... 55 °C (-13 ... 131 °F) |

Relative humidity

| | |
|----------------|-------------------------------------|
| Max. operation | 95 % RH, condensation not permitted |
|----------------|-------------------------------------|



Figure similar

MLFB-Ordering data

6SL3210-1PB21-0AL0

Mechanical data

| | |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Size | FSB |
| Net weight | 3.10 kg (6.83 lb) |
| Width | 100 mm (3.94 in) |
| Height | 292 mm (11.50 in) |
| Depth | 165 mm (6.50 in) |

Connections

Line side

| | |
|-------------------------|---|
| Version | Plug-in screw terminals |
| Conductor cross-section | 1.50 ... 6.00 mm ² (AWG 16 ... AWG 10) |


Motor end

| | |
|-------------------------|---|
| Version | Plug-in screw terminals |
| Conductor cross-section | 1.50 ... 6.00 mm ² (AWG 16 ... AWG 10) |

Converter losses to EN 50598-2*

Efficiency class ?PMD_ACF685_001_00 ?

Comparison with the reference converter (90% / 100%) -48.07 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length

| | |
|------------|-------------------|
| Shielded | 50 m (164.04 ft) |
| Unshielded | 100 m (328.08 ft) |

Standards

Compliance with standards UL, cUL, CE, C-Tick (RCM), SEMI F47

CE marking Low-voltage directive 2006/95/EC