



Figure similar

### MLFB-Ordering data

6SL3210-5HB10-4UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Communication	
<b>Input</b>		Communication	PROFINET
Number of phases	1 AC	<b>Ambient conditions</b>	
Line voltage	200 ... 240 V ±10 %	Installation altitude	1000 m (3280.84 ft)
Line frequency	45 ... 66 Hz	Cooling	convection cooling
Rated current	5.0 A	<b>Ambient temperature during</b>	
Inrush current	8.0 A	Operation	0 ... 50 °C (32 ... 122 °F)
<b>Output</b>			Better than class 3K3, in acc. with EN 60721-3-3, without derating
Number of phases	3 AC	Transport	-40 ... 70 °C (-40 ... 158 °F)
Rated power	0.40 kW ( 0.54 hp )		Class 2K4, in acc. with EN 60721-3-2, in transport packaging
Rated current I <sub>n</sub>	2.4 A	Storage	-25 ... 55 °C (-13 ... 131 °F)
Max. output current	8.7 A		Class 1K4, in acc. with EN 60721-3-1, in product packaging
Pulse frequency	8 kHz	<b>Relative humidity during</b>	
Output frequency for servo control	0 ... 550 Hz	Max. operation	95 %
<b>Electronics power supply</b>			RH, condensation not permitted
Voltage	24 V -15 % ... +20 %	Transport, max.	95 %
Current demand, max.	1.6 A		at 40 °C (104 °F)
		Bearing, max.	95 %



Figure similar

### Inputs / outputs

#### Standard digital inputs

Number	5
	of which 2 for F-DI

#### Fail-safe digital inputs

Number	1
	Can only be used for STO/SS1

### Mechanical data

#### Dimensions

Width	55.0 mm (2.17 in)
Height without shield plate	170.0 mm (6.69 in)
Depth	172.4 mm (6.79 in)
Mounting position	vertical wall mounting
Degree of protection	IP20 / UL open type
Size	FSB
Net weight	1.30 kg (2.87 lb )

### Connections

#### Line side

Version	push-in spring-type terminals
Conductor cross-section	0.2 ... 2.5 mm <sup>2</sup> / 24 ... 14 AWG

#### Motor end

Version	push-in spring-type terminals
Conductor cross-section	0.2 ... 2.5 mm <sup>2</sup> / 24 ... 14 AWG

#### DC link (for braking resistor)

Version	push-in spring-type terminals
Conductor cross-section	0.2 ... 2.5 mm <sup>2</sup> / 24 ... 14 AWG
Cable length	3 m (9.84 ft)

#### PE connection

Version	M4 screw studs
---------	----------------

#### Max. motor cable length

Shielded	50 m (164.04 ft)
----------	------------------

### Standards

Compliance with standards	CE, cULus, RCM, KC, EAC
---------------------------	-------------------------

CE marking	Low-voltage directive 2006/95/EC
------------	----------------------------------

#### Verification of suitability for fail-safety

SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)