



Delivered without miniature WSB markers

The 750-623 Series Power Supply Module generates 5V, 8V, 10V, 12V and 15VDC output voltages from the 24VDC input voltage. The output voltage is selected by a DIP switch located on the side of the module and can be accessed at the CAGE CLAMP® terminals. Downstream modules are supplied with the selected voltage via the power jumper contacts. LEDs indicate the module's operating state. The input voltage and the output voltage are not electrically isolated.

Description	Item No.	Pack. Unit
Supply Module DC 24V / 5-15V	750-623	1
<b>Accessories</b>		
<b>Miniature WSB Quick marking system</b>		
 plain	248-501	5
with marking	see Section 1.1	
<b>Approvals</b>		
Conformity marking	CE	
Korea Certification		
Marine applications	BV, GL, LR, NKK, PRS, RINA	
UL 508		
ANSI/ISA 12.12.01	Class I, Div. 2, Grp. ABCD, T4	
TÜV 07 ATEX 554086 X	I M2 Ex d I Mb, II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T135°C Dc	
IECEx TUN 09.0001 X	Ex d I Mb, Ex nA IIC T4 Gc, Ex tc IIIC T135°C Dc	

Technical Data	
Power supply	24 V DC (-15 % ... +20 %)
Output voltage	5 V, 8 V, 10 V, 12 V, 15 V DC
Output current	0.5 A (1 A at 5 V)
Wire connection	CAGE CLAMP®
Cross sections	0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> / AWG 28 ... 14
Strip lengths	8 ... 9 mm / 0.33 in
Width	12 mm
Weight	53.7 g
EMC immunity of interference	acc. to EN 61000-6-2, marine applications
EMC emission of interference	acc. to EN 61000-6-3, marine applications