

UL 4X CONVENIENCE POWER IN A BOX **HUBBELL**



- **UL Type 4X convenience power.**
- **Pre-wired devices for installation simplicity.**
- **All common NEMA configurations.**
- **Custom options available.**



**UL Type 4X Rated -
Conduit Feed**



**UL Type 3R Rated -
LINKOSITY™ Feed**



**UL Type 4X Rated -
LINKOSITY™ Feed**



**UL 4X Rated -
LINKOSITY™ Feed**

SPECIFICATIONS

Valox Enclosure	Corrosion, impact and chemical resistant.
Mounting Feet	External feet provide mounting adjustability.
Supply Options	Rigid, PVC, Flexible Conduit, LINKOSITY™.
Device Options	Straight Blade, Watertight Safety-Shroud™ Twist-Lock®, LINKOSITY.
Environmental	UL Type 3R, 12 (Straight Blade), UL Type 4, 4X, 12 and 13 (Watertight Safety-Shroud Twist-Lock).
Certifications	Listed to UL 5A.



Wiring Device-Kellems

UL 4X CONVENIENCE POWER IN A BOX **HUBBELL**



CONDUIT FEED - UL Type 4X Rated*

* Watertight Safety-Shroud™ Twist-Lock® Plug Required When In Use.

Device Type	Style	Type	No. of Devices	NEMA Device Type	Pass-Thru
M	C - Conduit Feed	WF - Watertight Safety-Shroud Receptacles	2	01 - 20A 125V Straight Blade	0 - No Pass-Thru
				02 - 20A 125V Twist-Lock	
				03 - 20A 250V Twist-Lock	
				04 - 20A 277V Twist-Lock	
				05 - 30A 125V Twist-Lock	
				06 - 30A 250V Twist-Lock	
		WM - Watertight Safety-Shroud Inlet		07 - 20A 125/250V Twist-Lock	
				08 - 20A 3Ø 250V Twist-Lock	
				09 - 20A 3Ø 480V Twist-Lock	
				10 - 30A 125/250V Twist-Lock	
				11 - 30A 3Ø 250V Twist-Lock	
				12 - 30A 3Ø 480V Twist-Lock	
				13 - 30A 3Ø 600V Twist-Lock	

Conduit Feed Stocked Boxes

Catalog No.	Description
MCWF2010	20A 125V Straight Blade
MCWF2020	20A 125V WTSSTL
MCWF2030	20A 250V WTSSTL
MCWF2040	20A 277V WTSSTL
MCWF2050	30A 125V WTSSTL
MCWF2060	30A 250V WTSSTL
MCWF2070	20A 125V/250V WTSSTL
MCWF2080	20A 3Ø, 250V WTSSTL
MCWF2090	20A 3Ø, 480V WTSSTL
MCWF2100	30A 125V/250V WTSSTL
MCWF2110	30A 3Ø 250V WTSSTL
MCWF2120	30A 3Ø 480V WTSSTL
MCWF2130	30A 3Ø 600V WTSSTL

Note: WTSSTL is an abbreviation for Watertight Safety-Shroud™ Twist-Lock®.

LINKOSITY™ - Plug & Play Power



LINKOSITY™ FEED - UL Type 3R Rated*

* When Not In Use Only.

Device Type	Style	Type	No. of Devices	Device Type	Device Feature	Pass-Thru
M	3R - 3R Lids 3D - 3R Deep Cover	SL - Switch Local	1	SG - Spec Grade	IG - Isolated Ground	P - Pass-Thru
		SM - Switch Master 00 - None	2	HG - Hospital Grade CR - Corrosion Resistant L1 - 15A Locking	GF - Ground Fault SI - Surge/IG SS - Surge 00 - Standard	0 - No Pass-Thru

3R Rated Stocked Items

Catalog No.	Description
M3R002SGGF0	20A 125V Ground Fault
M3RSL1SG000	20A 125V Switched, Spec Grade
M3RSL1SGGF0	20A 125V Switched, Ground Fault
M3R002SG000	20A 125V Spec Grade
M3R002SGGF0P	20A 125V Ground Fault, Pass-Thru
M3RSL1SG00P	20A 125V Switched, Spec Grade, Pass-Thru
M3RSL1SGGF0P	20A 125V Switched, Ground Fault, Pass-Thru
M3R002SG00P	Spec Grade, Pass-Thru

LINKOSITY™ FEED - UL Type 4X Rated*

* Watertight Safety-Shroud Twist-Lock Plug Required When In Use.

Device Type	Style	Type	No. of Devices	Device Type	Pass-Thru
M	L - Linkosity	WF - Watertight Safety-Shroud Receptacle	2	01 - 20A 125V Straight Blade	P - Pass-Thru 0 - No Pass-Thru
				02 - 20A 125V Twist-Lock	
				03 - 20A 250V Twist-Lock	
				04 - 20A 277V Twist-Lock	
				05 - 30A 125V Twist-Lock	
				06 - 30A 250V Twist-Lock	
		WM - Watertight Safety-Shroud Inlet		07 - 20A 125/250V Twist-Lock	
				08 - 20A 3Ø 250V Twist-Lock	
				09 - 20A 3Ø 480V Twist-Lock	
				10 - 30A 125/250V Twist-Lock	
				11 - 30A 3Ø 250V Twist-Lock	
				12 - 30A 3Ø 480V Twist-Lock	
				13 - 30A 3Ø 600V Twist-Lock	



4X Rated NEMA Stocked Items

Catalog No.	Description
MLWF2010	20A 125V Straight Blade
MLWF2020	20A 125V WTSSTL
MLWF201P	20A 125V Straight Blade, Pass-Thru
MLWF202P	20A 125V WTSSTL, Pass-Thru

Note: WTSSTL is an abbreviation for Watertight Safety-Shroud™ Twist-Lock®.

ALL LINKOSITY™ - UL Type 4X Rated

* Closure Cap Required When Not In Use.

Device Type	Style	Type	No. of Poles	Conductor Colors	Pass - Thru
M	4L - Linkosity	20 - 20A	02	PA - Green/Yellow Black (all others)	P - Pass-Thru 0 - No Pass-Thru
			03		
			04		
		23 - 20A Super Neutral Isolated Ground	05	PB - Green/Yellow White Black (all others)	
			03		
			04		
05					
06					
30 - 30A	04				



4X Rated Linkosity Stocked Items

Catalog No.	Description
M4L2003PB0	20A 3W up to 600V, 4 Port
M4L2003PBP	20A 3W up to 600V, 4 Port Pass-Thru

LINKOSITY™ is a Trademark of Lockheed Martin Corporation.

Printed In U.S.A. Specifications subject to change without notice. © Registered trademark of Hubbell Incorporated.

Hubbell Incorporated (Delaware) • 185 Plains Road • Milford, CT 06461-2420 • (203) 882-4800 • FAX (800) 255-1031

H5207-04/06

www.hubbell-wiring.com

