

LUTZE POWER SUPPLIES – DELTA SERIES

Single Phase

10 Watt, DC 5V, 2A



722761

93 Watt, DC 24V, 3.8A



722757

18 Watt, DC 24V, .75A



722752

120 Watt, DC 24V, 5A



722758

30 Watt, DC 24V, 1.25A



722753

240 Watt, DC 24V, 10A



722759

60 Watt, DC 24V, 2.5A



722754

480 Watt, DC 24V, 20A



722782

Three Phase

120 Watt, DC 24V, 5A



722803

240 Watt, DC 24V, 10A



722804

480 Watt, DC 24V, 20A



722805

General Specifications:

- 10 to 480 Watts
- Output voltages: 5V, 12V and 24V
- Output currents: 0.75 - 20A
- DIN rail mountable
- High efficiency: >93%
- Wide input voltage range:
AC 85-576V
- Short circuit protection
- Low heat dissipation

- Low ripple and noise: > 100mV
- Parallel & Redundant features
- Spring, screw and pluggable screw terminals available
- RoHS
- UL 508 Listed
- Output alarm relay
- Class 1 Div.2 units available
- 5-year warranty

Ask about our electronic DC circuit protection device LOCC-Box!

LUTZE Inc.
13330 South Ridge Drive
Charlotte, North Carolina 28273

1-800-447-2371
sales@lutze.com
www.lutze.com

LUTZE POWER SUPPLIES – COMPACT SERIES

Economy Single Phase

120 Watt, DC 24V, 5A



723500

240 Watt, DC 24V, 10A



723600

480 Watt, DC 24V, 20A



723701

Universal Single Phase

120 Watt, DC 24V, 5A



723501

240 Watt, DC 24V, 10A



723601

480 Watt, DC 24V, 20A



723700

Universal 1,2,3-Phase

240 Watt, DC 24V, 10A



722996

480 Watt, DC 24V, 20A



722801

General Specifications:

- 80 to 2400 Watts
- Output voltages: 24V, 48V, 72V
- Output current: 2.5 - 100A
- DIN rail mountable
- High efficiency >95%
- Wide input voltage range
AC 90-550V
- Short circuit protection

LUTZE Inc.
13330 South Ridge Drive
Charlotte, North Carolina 28273

Three Phase

720 Watt, DC 24V, 30A



722802

960 Watt, DC 24V, 40A



722811

- Low heat dissipation
- Low ripple and noise: <100mV
- Parallel & Redundant features
- Screw and pluggable screw terminals available
- RoHS
- UL 508 Listed
- 5-year warranty

1-800-447-2371
sales@lutze.com
www.lutze.com